Safety Data Sheet



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

Product Use: Industrial Oil
Product Number(s): 524601
Company Identification

Chevron Alkhalij

P.O. Box 2155, ENOC House II

Sheikh Rashid Road

Dubai

United Arab Emirates

Transportation Emergency Response

United Arab Emirates: +971-4-313-3966

Health Emergency

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800)

231-0623 or (510) 231-0623

Product Information

email: AELubricantsTechSupp@chevron.com

Product Information: +971-4-313-3944 SDS Requests: +971-4-313-3944

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION: Aspiration toxicant: Category 1.



Signal Word: Danger

Health Hazards: May be fatal if swallowed and enters airways (H304).

Revision Number: 0 1 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

PRECAUTIONARY STATEMENTS:

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician (P301+P310). Do

NOT induce vomiting (P331). **Storage:** Store locked up (P405).

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international

regulations (P501).

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

| COMPONENTS | CAS NUMBER | AMOUNT |
|--|------------|-----------------|
| Distillates, hydrotreated light naphthenic | 64742-53-6 | 50 - 70 %weight |
| Distillates, hydrotreated heavy paraffinic | 64742-54-7 | 0 - 50 %weight |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | 0 - 50 %weight |
| Lubricating oils, hydrotreated C15-30, neutral | 72623-86-0 | 0 - 50 %weight |
| oil-based | | |
| Distillates, solvent-refined heavy naphthenic | 64741-96-4 | 0 - 5 %weight |
| Distillates, solvent-refined light naphthenic | 64741-97-5 | 0 - 5 %weight |

This product is not approved for direct food use or use as a component of nonfood articles intended for use in contact with food.

SECTION 4 FIRST AID MEASURES

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs. **Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light

hydrocarbon liquid, which may cause pneumonitis.

IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Revision Number: 0 2 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

Ingestion: Highly toxic; may be fatal if swallowed. Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

DELAYED OR OTHER HEALTH EFFECTS:

Reproduction and Birth Defects: This material is not expected to cause adverse reproductive effects based on animal data.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities as appropriate or required.

SECTION 7 HANDLING AND STORAGE

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not taste or swallow. Wash thoroughly after handling.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves,

Revision Number: 0 3 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include:

Respiratory Protection: No respiratory protection is normally required. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

| occupational Exposure Entition | | | | | |
|---------------------------------|----------|---------|----------|---------|----------|
| Component | Country/ | TWA | STEL | Ceiling | Notation |
| | Agency | | | | |
| Distillates, hydrotreated light | ACGIH | 5 mg/m3 | 10 mg/m3 | | A2 |
| naphthenic | | | | | |
| Distillates, hydrotreated heavy | ACGIH | 5 mg/m3 | 10 mg/m3 | | |
| paraffinic | | | | | |
| Lubricating oils, hydrotreated | ACGIH | 5 mg/m3 | 10 mg/m3 | | |

Revision Number: 0 4 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

| C15-30, neutral oil-based | | | | |
|------------------------------------|-------|---------|------|----|
| Distillates, solvent-refined heavy | ACGIH | 5 mg/m3 | | A2 |
| naphthenic | | | | |
| Distillates, solvent-refined light | ACGIH | 5 mg/m3 | | A2 |
| naphthenic | | | | |

Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Colorless to yellow **Physical State:** Viscous liquid

Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Vapor Pressure: <0.01 kPa (Estimated) @ 23 °C (73.4 °F)

Vapor Density (Air = 1): No data available Boiling Point: 250°C (482°F) Minimum

Solubility: Insoluble in water; miscible with most organic solvents.

Freezing Point: Not Applicable Melting Point: No data available Specific Gravity: 0.87 (Typical)

Density: 0.8762 kg/l @ 20°C (68°F) (Typical) **Viscosity:** 9.80 mm2/s @ 40°C (104°F) (Typical)

Evaporation Rate: No data available

Octanol/Water Partition Coefficient: 6 log Kow Minimum

FLAMMABLE PROPERTIES:

Flashpoint: (Pensky-Martens Closed Cup) 135 °C (275 °F) Minimum

Autoignition: 250 °C (482 °F)

Flammability (Explosive) Limits (% by volume in air): Lower: No data available Upper: No data

available

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected) **Hazardous Polymerization:** Hazardous polymerization will not occur.

Revision Number: 0 5 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

SECTION 11 TOXICOLOGICAL INFORMATION

Eye Irritation: The eye irritation hazard is based on evaluation of data for similar materials.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for similar materials.

Skin Irritation: The skin irritation hazard is based on evaluation of data for similar materials.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for similar materials.

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for similar materials.

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for similar materials.

Acute Toxicity Estimate: Not Determined

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from products of a similar structure and composition.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from products of a similar structure and composition.

Revision Number: 0 6 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Octanol/Water Partition Coefficient: 6 log Kow Minimum

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: NOT REGULATED AS A HAZARDOUS MATERIAL UNDER 49 CFR

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1 01-2A=IARC Group 2A 01-2B=IARC Group 2B

The following components of this material are found on the regulatory lists indicated.

Distillates, hydrotreated light naphthenic 01-1

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), NZIoC (New

Revision Number: 0 7 of 8 Caltex Transformer Oil Pro-eleKt 9 - Uninhibited

Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: This is a new Safety Data Sheet. No revision information

Revision Date: February 21, 2018

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

| TLV - Threshold Limit Value | TWA - Time Weighted Average | |
|---|--|--|
| STEL - Short-term Exposure Limit | PEL - Permissible Exposure Limit | |
| | CAS - Chemical Abstract Service Number | |
| ACGIH - American Conference of Governmental | IMO/IMDG - International Maritime Dangerous Goods | |
| Industrial Hygienists | Code | |
| API - American Petroleum Institute | SDS - Safety Data Sheet | |
| CVX - Chevron | NFPA - National Fire Protection Association (USA) | |
| | | |
| | NTP - National Toxicology Program (USA) | |
| IARC - International Agency for Research on | OSHA - Occupational Safety and Health Administration | |

Prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) by the Chevron Energy Technology Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

8 of Revision Number: 0 Uninhibited Revision Date: February 21, 2018

SDS: 46941

Caltex Transformer Oil Pro-eleKt 9 -